


PRODUCT CONFIGURATIONS



EE-0427

Low-Profile Bulk Bag Discharger Fits Existing Layouts



flexicon®

USA

FLEXICON CORPORATION
Tel: 1 888 FLEXICON
(1 888 353 9426)
Tel: 1 610 814 2400
E-mail: sales@flexicon.com
Web: www.flexicon.com

UK

FLEXICON (EUROPE) LTD
Tel: +44 (0)1227 374710
E-mail: sales@flexicon.co.uk
Web: www.flexicon.co.uk

AUSTRALIA

FLEXICON CORPORATION
(AUSTRALIA) PTY LTD
Tel: +61 (0)7 3879 4180
E-mail: sales@flexicon.com.au
Web: www.flexicon.com.au

SOUTH AFRICA

FLEXICON AFRICA (PTY) LTD
Tel: +27 (0)41 453 1871
E-mail: sales@flexicon.co.za
Web: www.flexicon.co.za

SPAIN

FLEXICON EUROPE SPAIN S.L.
Tel: +34 930 020 509
E-mail: ventas@flexicon.es
Web: www.flexicon.es

FRANCE

FLEXICON (EUROPE) LTD
Tel: +33 (0)7 61 36 56 12
E-mail: ventes@flexicon.fr
Web: www.flexicon.fr

GERMANY

FLEXICON EUROPE GmbH
Tel: +49 173 900 78 76
E-mail: vertrieb@flexiconeurope.de
Web: www.flexicondeutschland.de

SINGAPORE

FLEXICON SINGAPORE PTE LTD
Tel: +65 6778 9225
E-mail: sales@flexicon.com.sg
Web: www.flexicon.com.sg

INDONESIA

FLEXICON SINGAPORE PTE LTD
Tel: +62 81 1103 2400
E-mail: sales@flexicon.co.id
Web: www.flexicon.co.id

MALAYSIA

FLEXICON SINGAPORE PTE LTD
Tel: +60 10 282 2400
E-mail: sales@flexicon.com.my
Web: www.flexicon.com.my

Low-Profile Bulk Bag Discharger Fits Existing Layouts

This series of BULK-OUT® Half-Frame Bulk Bag Dischargers features low-cost frames of variable heights and offsets to fit restricted areas previously utilized for dumping of smaller containers such as sacks, pails drums, boxes and bins.

The low profile dischargers are engineered to straddle downstream blenders, feeders, tanks or other equipment in areas with limited headroom, restricted floor space and/or obstacles that would preclude the use of conventional discharger frames.

Lacking an upper frame, the discharger provides overhead space for suspending of bulk bags using a forklift or plant hoist. It can also be configured to support new or existing bulk bag lifting frames that can be connected to bags at floor level and then forklifted onto the half frame within inches/centimeters of the ceiling.

The bag-to-discharger interface consists of a SPOUT-LOCK® clamp ring positioned atop a pneumatically actuated TELE-TUBE® telescoping tube, allowing dust-tight connections. The telescoping tube raises the clamp ring assembly that seals the clean side of the bag spout to the clean side of the telescoping tube, and applies constant downward tension to the bag as it empties and elongates, promoting complete evacuation.

The high-integrity, dust-tight seal between bag spout and clamp ring allows full-open discharge from bag spouts of all popular diameters, eliminating the need for iris valves commonly employed to lessen dust escape inherent with bag spouts hanging loosely within intake chutes.

The discharger is also equipped with FLOW-FLEXER® bag activators that raise and lower opposite bottom edges of the bag at timed intervals, loosening compacted materials and promoting material flow through the bag discharge spout. As the bag lightens, the stroke of the bag activators increases, raising the bag into a steep "V" shape, eliminating dead spots for total evacuation of material with no manual intervention.

Product contact surfaces are of stainless steel, with frame construction of carbon steel, or stainless steel finished to industrial, food, dairy or pharmaceutical standards.

Full-frame dischargers offered by the company include BFF models with a lifting frame for forklift loading of bulk bags, and BFC models with a cantilevered I-beam and electric hoist and trolley for positioning of bags without the use of a forklift.



The variable height and offsets of low profile BULK-OUT® Half-Frame Dischargers allow dust-free evacuation of bulk bags in restricted spaces at low cost.