


PRODUCT CONFIGURATIONS



GG-0594A

Dust-Tight Drum Dumper for Difficult Materials



flexicon®

USA

FLEXICON CORPORATION
Tel: 1 888 FLEXICON
(1 888 353 9426)
Tel: 1 610 814 2400
E-mail: sales@flexicon.com
Web: www.flexicon.com

UK

FLEXICON (EUROPE) LTD
Tel: +44 (0)1227 374710
E-mail: sales@flexicon.co.uk
Web: www.flexicon.co.uk

AUSTRALIA

FLEXICON CORPORATION
(AUSTRALIA) PTY LTD
Tel: +61 (0)7 3879 4180
E-mail: sales@flexicon.com.au
Web: www.flexicon.com.au

SOUTH AFRICA

FLEXICON AFRICA (PTY) LTD
Tel: +27 (0)41 453 1871
E-mail: sales@flexicon.co.za
Web: www.flexicon.co.za

SPAIN

FLEXICON EUROPE SPAIN S.L.
Tel: +34 930 020 509
E-mail: ventas@flexicon.es
Web: www.flexicon.es

FRANCE

FLEXICON (EUROPE) LTD
Tel: +33 (0)7 61 36 56 12
E-mail: ventes@flexicon.fr
Web: www.flexicon.fr

GERMANY

FLEXICON EUROPE GmbH
Tel: +49 173 900 78 76
E-mail: vertrieb@flexiconeurope.de
Web: www.flexicondeutschland.de

SINGAPORE

FLEXICON SINGAPORE PTE LTD
Tel: +65 6778 9225
E-mail: sales@flexicon.com.sg
Web: www.flexicon.com.sg

INDONESIA

FLEXICON SINGAPORE PTE LTD
Tel: +62 81 1103 2400
E-mail: sales@flexicon.co.id
Web: www.flexicon.co.id

MALAYSIA

FLEXICON SINGAPORE PTE LTD
Tel: +60 10 282 2400
E-mail: sales@flexicon.com.my
Web: www.flexicon.com.my

Dust-Tight Drum Dumper for Difficult Materials

This TIP-TITE® drum dumper is designed for use with poorly-flowing or agglomerated materials, allowing rapid transfer of free- and non-free-flowing bulk solid materials dust-free. Similar in performance to open chute dumpers but with total dust containment, the outlet on the downstream end of the dumper is nearly equal in area to that of the drum opening, allowing agglomerated materials and large chunks to be discharged with minimal possibility of material bridging.

Drums from 30 to 55 gal (115 to 200 liters) are positioned on the dumper platform, which is raised by a hydraulic cylinder, seating the rim against the circular end of the discharge transition. A second hydraulic cylinder tips the platform-hood assembly and drum, stopping at dump angles of 45, 60 or 90 degrees with a motion-dampening feature. At full rotation, the transition outlet mates with the gasketed square inlet on the lid of a hopper or downstream process equipment, allowing a pneumatically-actuated slide gate valve to be opened and closed for total or partial discharge with no dusting.

The stainless steel transition can be supplied with a square or rectangular outlet as shown, as well as with circular outlets, with corresponding gasketed flanges for installation on downstream hoppers and receiving vessels.

Non-product-contact materials of construction can be specified in carbon steel with durable industrial finishes, or stainless steel finished to industrial or sanitary standards.

Other models are available for dumping of boxes, bins, pails and other containers.



TIP-TITE® drum dumper for poorly-flowing or agglomerated materials, allows rapid transfer of bulk solid materials dust-free.