

PRODUCT CONFIGURATIONS



X-0668

Bulk Bag Filling Line



flexicon®

USA
FLEXICON CORPORATION
Tel: 1 888 FLEXICON
(1 888 353 9426)
Tel: 1 610 814 2400
E-mail: sales@flexicon.com
Web: www.flexicon.com

UK
FLEXICON (EUROPE) LTD
Tel: +44 (0)1227 374710
E-mail: sales@flexicon.co.uk
Web: www.flexicon.co.uk

AUSTRALIA
FLEXICON CORPORATION
(AUSTRALIA) PTY LTD
Tel: +61 (0)7 3879 4180
E-mail: sales@flexicon.com.au
Web: www.flexicon.com.au

SOUTH AFRICA
FLEXICON AFRICA (PTY) LTD
Tel: +27 (0)41 453 1871
E-mail: sales@flexicon.co.za
Web: www.flexicon.co.za

SPAIN
FLEXICON EUROPE SPAIN S.L.
Tel: +34 930 020 509
E-mail: ventas@flexicon.es
Web: www.flexicon.es

FRANCE
FLEXICON (EUROPE) LTD
Tel: +33 (0)7 61 36 56 12
E-mail: ventes@flexicon.fr
Web: www.flexicon.fr

GERMANY
FLEXICON EUROPE GmbH
Tel: +49 173 900 78 76
E-mail: vertrieb@flexicon-europe.de
Web: www.flexicon-deutschland.de

SINGAPORE
FLEXICON SINGAPORE PTE LTD
Tel: +65 6778 9225
E-mail: sales@flexicon.com.sg
Web: www.flexicon.com.sg

INDONESIA
FLEXICON SINGAPORE PTE LTD
Tel: +62 81 1103 2400
E-mail: sales@flexicon.co.id
Web: www.flexicon.co.id

MALAYSIA
FLEXICON SINGAPORE PTE LTD
Tel: +60 10 282 2400
E-mail: sales@flexicon.com.my
Web: www.flexicon.com.my

Bulk Bag Filling Line

This Bulk Bag Filling Line from Flexicon automatically dispenses pallets, fills bulk bags, and accumulates filled bags for removal by forklift.

The dispenser, which holds up to 15 pallets, is equipped with a powered roller conveyor that removes the bottom-most pallet from the stack, and positions it directly beneath the cantilevered fill head of a bulk bag filler.

An operator then connects an empty bag to four actuated bag strap hooks, seals the bag spout using an inflatable collar, and presses a bag inflation button to initiate a seven-step automated filling sequence: 1) start a conveyor to fill the bag at high rate, 2) reduce the feed rate to dribble speed as the target weight is approached, 3) stop the conveyor once the target rate is achieved, 4) vibrate the pallet to densify and stabilize the bag, 5) deflate the spout seal, 6) release the bag loops and 7) release the pallet with newly filled bag (and any previously filled bags) to roll to the furthest of three downstream conveyor positions.

The filler is equipped with a powered fill head height adjustment that accommodates all popular bag sizes, and a feed chute vent for dust-free air displacement during filling. An optional SWING-DOWN® fill head lowers and pivots to a vertical position, allowing operators to connect empty bags at floor level at high rates.

The system is offered with the company's own mechanical or pneumatic material delivery system integrated with the user's upstream process equipment or other material source.

All system components are available constructed to industrial, food, dairy and pharmaceutical standards.



A 15-pallet dispenser releases the bottom-most pallet to roll beneath the cantilevered fill head of a bulk bag filler. Following manual connection of empty bags to the fill head, filling, densification and conveying functions are automatic.