




Base Model Carbon Steel Flexible Screw Conveyor

II-0796



flexicon®

USA

FLEXICON CORPORATION
Tel: +1 610 814 2400
E-mail: sales@flexicon.com
Web: www.flexicon.com

UK

FLEXICON (EUROPE) LTD
Tel: +44 1227 374710
E-mail: sales@flexicon.co.uk
Web: www.flexicon.co.uk

AUSTRALIA

FLEXICON CORPORATION (AUSTRALIA) PTY LTD
Tel: +61 7 3879 4180
E-mail: sales@flexicon.com.au
Web: www.flexicon.com.au

SOUTH AFRICA

FLEXICON AFRICA (PTY) LTD
Tel: +27 41 453 1871
E-mail: sales@flexicon.co.za
Web: www.flexicon.co.za

SPAIN

FLEXICON EUROPE SPAIN
Tel: +34 930 020 509
E-mail: ventas@flexicon.es
Web: www.flexicon.es

FRANCE

FLEXICON EUROPE SAS
Tel: +33 7 61 36 56 12
E-mail: ventes@flexicon.fr
Web: www.flexicon.fr

GERMANY

FLEXICON EUROPE GmbH
Tel: +49 173 900 78 76
E-mail: vertrieb@flexicon-europe.de
Web: www.flexicon-deutschland.de

SINGAPORE

FLEXICON SINGAPORE PTE LTD
Tel: +65 6778 9225
E-mail: sales@flexicon.com.sg
Web: www.flexicon.com.sg

INDONESIA

FLEXICON SINGAPORE PTE LTD
Tel: +62 81 1103 2400
E-mail: sales@flexicon.co.id
Web: www.flexicon.co.id

Base Model Carbon Steel Flexible Screw Conveyor

Flexicon has introduced a base model 1450 flexible screw conveyor with 4-1/2 inch (114 mm) O.D. polymer conveyor tube and low cost carbon steel floor hopper and discharge housing. Round, square, flat or beveled flexible screws in any length from 10 to 40 feet (3 to 12 m) are offered to convey virtually any free- and non-free-flowing bulk material including products that pack, cake, seize, smear or break apart, with no separation of blends.

The only moving part contacting material is the inner screw, which self-centers as it rotates, providing ample space between the screw and tube wall to minimize or eliminate grinding. The lower end of the screw requires no bearing, while the upper end is driven beyond the point of discharge, preventing material contact with bearings or seals.

Fully enclosed, the conveyor tube prevents product and plant contamination, while the gentle rolling action imparted by the screw prevents the separation of blends.

Model 1450 is available with an optional UL listed start-stop control panel and a range of flow-promotion devices, and is available on a Quick Ship basis in the Americas and in Europe.



Flexicon Flexible Screw Conveyor Model 1450 can handle diverse materials ranging in size from large pellets to sub-micron powders with no separation of blends.

flexicon[®]

USA

FLEXICON CORPORATION
Tel: +1 610 814 2400
E-mail: sales@flexicon.com
Web: www.flexicon.com