


FLEXICON CONFIGURATIONS



All-Steel Flexible Screw Conveyor Resists Abrasion

II-0461



flexicon®

USA

FLEXICON CORPORATION
Tel: +1 610 814 2400
E-mail: sales@flexicon.com
Web: www.flexicon.com

UK

FLEXICON (EUROPE) LTD
Tel: +44 1227 374710
E-mail: sales@flexicon.co.uk
Web: www.flexicon.co.uk

AUSTRALIA

FLEXICON CORPORATION (AUSTRALIA) PTY LTD
Tel: +61 7 3879 4180
E-mail: sales@flexicon.com.au
Web: www.flexicon.com.au

SOUTH AFRICA

FLEXICON AFRICA (PTY) LTD
Tel: +27 41 453 1871
E-mail: sales@flexicon.co.za
Web: www.flexicon.co.za

SPAIN

FLEXICON EUROPE SPAIN
Tel: +34 930 020 509
E-mail: ventas@flexicon.es
Web: www.flexicon.es

FRANCE

FLEXICON EUROPE SAS
Tel: +33 7 61 36 56 12
E-mail: ventes@flexicon.fr
Web: www.flexicon.fr

GERMANY

FLEXICON EUROPE GmbH
Tel: +49 173 900 78 76
E-mail: vertrieb@flexicon-europe.de
Web: www.flexicon-deutschland.de

SINGAPORE

FLEXICON SINGAPORE PTE LTD
Tel: +65 6778 9225
E-mail: sales@flexicon.com.sg
Web: www.flexicon.com.sg

INDONESIA

FLEXICON SINGAPORE PTE LTD
Tel: +62 81 1103 2400
E-mail: sales@flexicon.co.id
Web: www.flexicon.co.id

All-Steel Flexible Screw Conveyor Resists Abrasion

Flexicon's wear-resistant flexible screw conveyor with carbon steel conveyor tube, heavy-duty flexible screw, and heavy-gauge floor hopper and discharge housing, can move crushed glass, garnet, aluminum oxide, silica sand, aggregate, cement and other abrasive materials.

The screw is available in lengths up to 40 feet (12 m) in round, square, flat or beveled profiles to optimize conveying efficiency for each application. The 4-1/2 inch (115 mm) diameter conveyor tube is available curved to vertical, to horizontal or at any angle.

The screw is the only moving part contacting material. Its lower end has no bearing, while its upper end is driven beyond material discharge point, preventing material contact with the upper seal or bearing. This configuration facilitates simple maintenance in harsh environments since the single moving component can be quickly replaced if necessary.

As it rotates, the screw self-centers, providing ample space between itself and tube wall to minimize or eliminate grinding. The gentle rolling action imparted by the screw prevents the separation of blends, while the enclosed conveyor tube prevents product and plant contamination.

Supplied as standard with a durable industrial coating, the unit is available with an optional UL-listed start-stop control panel and a range of flow-promotion devices.



Flexicon all-steel flexible screw conveyor conveys crushed glass, garnet, aluminum oxide, silica sand, aggregate, cement and other abrasive materials dust-free.

flexicon®

USA

FLEXICON CORPORATION
Tel: +1 610 814 2400
E-mail: sales@flexicon.com
Web: www.flexicon.com