



Bulk Bag Lifting Frame with Adjustable Arms

EE-0466



flexicon®

USA

FLEXICON CORPORATION
Tel: +1 610 814 2400
E-mail: sales@flexicon.com
Web: www.flexicon.com

UK

FLEXICON (EUROPE) LTD
Tel: +44 1227 374710
E-mail: sales@flexicon.co.uk
Web: www.flexicon.co.uk

AUSTRALIA

FLEXICON CORPORATION
(AUSTRALIA) PTY LTD
Tel: +61 7 3879 4180
E-mail: sales@flexicon.com.au
Web: www.flexicon.com.au

SOUTH AFRICA

FLEXICON AFRICA (PTY) LTD
Tel: +27 41 453 1871
E-mail: sales@flexicon.co.za
Web: www.flexicon.co.za

SPAIN

FLEXICON EUROPE SPAIN
Tel: +34 930 020 509
E-mail: ventas@flexicon.es
Web: www.flexicon.es

FRANCE

FLEXICON EUROPE SAS
Tel: +33 7 61 36 56 12
E-mail: ventes@flexicon.fr
Web: www.flexicon.fr

GERMANY

FLEXICON EUROPE GmbH
Tel: +49 173 900 78 76
E-mail: vertrieb@flexiconeurope.de
Web: www.flexicondeutschland.de

SINGAPORE

FLEXICON SINGAPORE PTE LTD
Tel: +65 6778 9225
E-mail: sales@flexicon.com.sg
Web: www.flexicon.com.sg

INDONESIA

FLEXICON SINGAPORE PTE LTD
Tel: +62 81 1103 2400
E-mail: sales@flexicon.co.id
Web: www.flexicon.co.id

Bulk Bag Lifting Frame with Adjustable Arms

This bulk bag lifting frame with telescoping arms accommodates bulk bags produced in an increasing range of sizes.

The lifting frame is optional on all BFC models of Flexicon's BULK-OUT® discharger line, and available for up to 2.2 ton (2 tonne) capacities to replace conventional lifting frames of any make or model of discharger that employs a hoist to position and suspend bulk bags.

The telescoping arms can be adjusted using clevis pins and safety clips to a range of settings to accommodate bulk bags from 32 to 47 in. (81 to 119 cm) square at the upper sew seam.

Available in carbon steel with durable industrial coatings or stainless steel to industrial or sanitary standards, the adjustable frames are equipped as standard with Flexicon's patented Z-CLIP™ strap channels that hold the straps securely while allowing rapid insertion and removal.

Other dischargers offered by the company include BFF models with a lifting frame for forklift loading of bulk bags, low-profile BFH half frame models that require a forklift or plant hoist to suspend the bag during unloading, and BFX split frame unloaders that allow loading of the upper frame on the plant floor, and then forklifting it onto the sub frame within several inches/centimeters of the ceiling.



New bulk bag lifting frames in 2.2 ton (2 tonne) capacity (shown) and 1.1 ton (1 tonne) capacity feature telescoping arms that accommodate bulk bags from 32 to 47 in. (81 to 119 cm) square.

flexicon®

USA

FLEXICON CORPORATION
Tel: +1 610 814 2400
E-mail: sales@flexicon.com
Web: www.flexicon.com