



Dual-Arch Bulk Bag Conditioner

LL-0480



📍 Flexicon manufacturing locations
■ Flexicon factory-direct field sales
■ Flexicon manufacturers' representatives

USA

FLEXICON CORPORATION
Tel: +1 610 814 2400
E-mail: sales@flexicon.com
Web: www.flexicon.com

UK

FLEXICON (EUROPE) LTD
Tel: +44 1227 374710
E-mail: sales@flexicon.co.uk
Web: www.flexicon.co.uk

AUSTRALIA

FLEXICON CORPORATION
(AUSTRALIA) PTY LTD
Tel: +61 7 3879 4180
E-mail: sales@flexicon.com.au
Web: www.flexicon.com.au

SOUTH AFRICA

FLEXICON AFRICA (PTY) LTD
Tel: +27 41 453 1871
E-mail: sales@flexicon.co.za
Web: www.flexicon.co.za

SPAIN

FLEXICON EUROPE SPAIN
Tel: +34 930 020 509
E-mail: ventas@flexicon.es
Web: www.flexicon.es

FRANCE

FLEXICON EUROPE SAS
Tel: +33 7 61 36 56 12
E-mail: ventes@flexicon.fr
Web: www.flexicon.fr

GERMANY

FLEXICON EUROPE GmbH
Tel: +49 173 900 78 76
E-mail: vertrieb@flexiconeurope.de
Web: www.flexicondeutschland.de

SINGAPORE

FLEXICON SINGAPORE PTE LTD
Tel: +65 6778 9225
E-mail: sales@flexicon.com.sg
Web: www.flexicon.com.sg

INDONESIA

FLEXICON SINGAPORE PTE LTD
Tel: +62 81 1103 2400
E-mail: sales@flexicon.co.id
Web: www.flexicon.co.id

Dual-Arch Bulk Bag Conditioner

This BLOCK-BUSTER® Hydraulic Bulk Bag Conditioner from Flexicon features arched doorway masts that increase overhead clearance for easier insertion and removal of palletized bulk bags using a forklift.

The conditioner loosens hygroscopic chemicals, spice blends, heat-sensitive products, and other bulk materials that have solidified during storage and shipment, returning the material to a free-flowing state and enabling bulk bag unloaders to discharge the material through bag spouts.

A hydraulically-actuated, variable-height turntable operates in concert with two hydraulic rams to press opposing sides of the bulk bag at varying heights, rotate the bag 90 degrees, and then repeat the conditioning cycle.

The number and pressure of hydraulic ram actuations, the height of the turntable, and the number of 90-degree rotations are user programmable at the control panel's HMI.

Enclosed on four sides, the conditioner is equipped with full-height, safety-interlocked doors that disable all equipment functions when the doors are open.

The system's hydraulic pump can be mounted on the exterior of the safety cage or remotely, and requires only an electrical power connection for operation.

Available through Flexicon's Quick-Ship Program as a stand-alone unit, the conditioner accommodates bulk bags of all popular sizes. It is also available constructed of stainless steel for sanitary and corrosive applications, and in configurations integral to bulk bag dischargers that reduce the cost, footprint and loading time of separate equipment.



Flexicon's Dual-arch Bulk Bag Conditioner increases overhead clearance for easier insertion and removal of palletized bulk bags using a forklift.

flexicon®

USA

FLEXICON CORPORATION
Tel: +1 610 814 2400
E-mail: sales@flexicon.com
Web: www.flexicon.com