



Flexible Screw Conveyor for Front End Loader

EE-0636



● Flexicon manufacturing locations
■ Flexicon factory-direct field sales
■ Flexicon manufacturers' representatives

flexicon®

USA

FLEXICON CORPORATION
Tel: +1 610 814 2400
E-mail: sales@flexicon.com
Web: www.flexicon.com

UK

FLEXICON (EUROPE) LTD
Tel: +44 1227 374710
E-mail: sales@flexicon.co.uk
Web: www.flexicon.co.uk

AUSTRALIA

FLEXICON CORPORATION
(AUSTRALIA) PTY LTD
Tel: +61 7 3879 4180
E-mail: sales@flexicon.com.au
Web: www.flexicon.com.au

SOUTH AFRICA

FLEXICON AFRICA (PTY) LTD
Tel: +27 41 453 1871
E-mail: sales@flexicon.co.za
Web: www.flexicon.co.za

SPAIN

FLEXICON EUROPE SPAIN
Tel: +34 930 020 509
E-mail: ventas@flexicon.es
Web: www.flexicon.es

FRANCE

FLEXICON EUROPE SAS
Tel: +33 7 61 36 56 12
E-mail: ventes@flexicon.fr
Web: www.flexicon.fr

GERMANY

FLEXICON EUROPE GmbH
Tel: +49 173 900 78 76
E-mail: vertrieb@flexiconeurope.de
Web: www.flexicondeutschland.de

SINGAPORE

FLEXICON SINGAPORE PTE LTD
Tel: +65 6778 9225
E-mail: sales@flexicon.com.sg
Web: www.flexicon.com.sg

INDONESIA

FLEXICON SINGAPORE PTE LTD
Tel: +62 81 1103 2400
E-mail: sales@flexicon.co.id
Web: www.flexicon.co.id

Flexible Screw Conveyor for Front End Loader

This extreme-duty Flexicon® flexible screw conveyor with purpose-built hopper transfers bulk material received from front end loaders.

The conveyor consists of a heavy-gauge stainless steel screw that rotates within an 8 in. dia. (200 mm) stainless steel tube. Since the conveyor is driven at its top end by a 20 hp (15 kW) variable speed electric motor and gear reducer, material exits the discharge housing prior to contacting any seals or bearings. The tube interior and removable screw are smooth and crevice-free, allowing rapid, thorough cleaning.

Rugged enough to withstand incidental contact with front-end loaders, the heavy-gauge stainless steel hopper holds up to 8 tons (7 tonnes), or 120 cu ft (3.4 m³), providing an ample supply of material for the high capacity conveyor to run continually as a front end loader replenishes the material.

Self-contained on an all-stainless skid equipped with forklifting tubes, the system can be deployed in multiple indoor or outdoor locations with a single power connection, conveying a broad range of free-flowing and non-free-flowing materials from fine powders to large aggregates including abrasives, corrosives and materials with bulk densities up to 150 lb/cu ft (2400 kg/m³).

Material is conveyed at a 40 degree incline before discharging into downstream processing equipment or storage vessels.

The simple design delivers efficient performance and high reliability while reducing maintenance and cost.

The system is also available constructed of carbon steel with durable industrial coatings.



New extreme-duty stainless steel Flexible Screw Conveying System from Flexicon can be forklifted to multiple plant locations to transfer materials sourced by front end loaders at high rates.

flexicon®

USA

FLEXICON CORPORATION
Tel: +1 610 814 2400
E-mail: sales@flexicon.com
Web: www.flexicon.com