






Drum Dumper Mates with Low-Height Receiving Vessels

FF-0600



 Flexicon manufacturing locations
 Flexicon factory-direct field sales
 Flexicon manufacturers' representatives

flexicon®

USA

FLEXICON CORPORATION
Tel: +1 610 814 2400
E-mail: sales@flexicon.com
Web: www.flexicon.com

UK

FLEXICON (EUROPE) LTD
Tel: +44 1227 374710
E-mail: sales@flexicon.co.uk
Web: www.flexicon.co.uk

AUSTRALIA

FLEXICON CORPORATION
(AUSTRALIA) PTY LTD
Tel: +61 7 3879 4180
E-mail: sales@flexicon.com.au
Web: www.flexicon.com.au

SOUTH AFRICA

FLEXICON AFRICA (PTY) LTD
Tel: +27 41 453 1871
E-mail: sales@flexicon.co.za
Web: www.flexicon.co.za

SPAIN

FLEXICON EUROPE SPAIN
Tel: +34 930 020 509
E-mail: ventas@flexicon.es
Web: www.flexicon.es

FRANCE

FLEXICON EUROPE SAS
Tel: +33 7 61 36 56 12
E-mail: ventes@flexicon.fr
Web: www.flexicon.fr

GERMANY

FLEXICON EUROPE GmbH
Tel: +49 173 900 78 76
E-mail: vertrieb@flexiconeurope.de
Web: www.flexicondeutschland.de

SINGAPORE

FLEXICON SINGAPORE PTE LTD
Tel: +65 6778 9225
E-mail: sales@flexicon.com.sg
Web: www.flexicon.com.sg

INDONESIA

FLEXICON SINGAPORE PTE LTD
Tel: +62 81 1103 2400
E-mail: sales@flexicon.co.id
Web: www.flexicon.co.id

Drum Dumper Mates with Low-Height Receiving Vessels

This TIP-TITE® Drum Dumper for 30 to 55 gallon (115 to 200 liter) drums features an elongated discharge cone that mates with the gasketed inlet of low-height receiving vessels, allowing dust-free transfer of free-flowing bulk solid materials.

Housed within a three-sided safety enclosure with safety interlocked doors, the drum platform is raised by a single hydraulic cylinder, creating a dust-tight seal between the rim of a drum and the underside of the discharge cone.

With drum secured in place, a second hydraulic cylinder tips the platform-hood assembly, stopping at a dump angle of 45 degrees with a motion-dampening feature, causing the spout of the discharge cone to mate with a gasketed receiving ring on the lid of a low-height receiving vessel. A pneumatically actuated slide gate at the spout can be opened variably for partial or total discharge at controlled rates, and then closed before returning the drum to its original position, with no dust emitted throughout the cycle.

Available in stationary and mobile configurations, the Drum Dumper is offered in carbon steel with durable industrial finishes, with material contact surfaces of stainless steel or in all-stainless steel finished to food, dairy, pharmaceutical or industrial standards. A diameter adapter allows for the safe and dust-tight dumping of smaller-diameter drums.



TIP-TITE® Drum Dumper with elongated discharge cone seals the drum rim before tipping the drum, seating the spout of the discharge cone against a gasketed receiving ring on vessel lids for dust-free discharging.

flexicon®

USA

FLEXICON CORPORATION
Tel: +1 610 814 2400
E-mail: sales@flexicon.com
Web: www.flexicon.com