



Low-Profile Flexible Screw Conveyor Rolls Under Mezzanines, Discharges Anywhere

GG-0384



USA

FLEXICON CORPORATION
Tel: +1 610 814 2400
E-mail: sales@flexicon.com
Web: www.flexicon.com

UK

FLEXICON (EUROPE) LTD
Tel: +44 1227 374710
E-mail: sales@flexicon.co.uk
Web: www.flexicon.co.uk

AUSTRALIA

FLEXICON CORPORATION
(AUSTRALIA) PTY LTD
Tel: +61 7 3879 4180
E-mail: sales@flexicon.com.au
Web: www.flexicon.com.au

SOUTH AFRICA

FLEXICON AFRICA (PTY) LTD
Tel: +27 41 453 1871
E-mail: sales@flexicon.co.za
Web: www.flexicon.co.za

SPAIN

FLEXICON EUROPE SPAIN
Tel: +34 930 020 509
E-mail: ventas@flexicon.es
Web: www.flexicon.es

FRANCE

FLEXICON EUROPE SAS
Tel: +33 7 61 36 56 12
E-mail: ventes@flexicon.fr
Web: www.flexicon.fr

GERMANY

FLEXICON EUROPE GmbH
Tel: +49 173 900 78 76
E-mail: vertrieb@flexiconeurope.de
Web: www.flexicondeutschland.de

SINGAPORE

FLEXICON SINGAPORE PTE LTD
Tel: +65 6778 9225
E-mail: sales@flexicon.com.sg
Web: www.flexicon.com.sg

INDONESIA

FLEXICON SINGAPORE PTE LTD
Tel: +62 81 1103 2400
E-mail: sales@flexicon.co.id
Web: www.flexicon.co.id

Low-Profile Flexible Screw Conveyor Rolls Under Mezzanines, Discharges Anywhere

This Low Profile Flexible Screw Conveyor with integral bin and caster-mounted frame can roll below mezzanines and other low-headroom areas, receive material from overhead equipment, and discharge the material into process equipment and vessels throughout the plant.

Ready to plug-in and run, the self-contained unit features a “push type” drive system positioned at the lower intake end of the conveyor, versus a standard “pull-type” drive positioned at the upper discharge end of the conveyor, reducing overall height by approximately 2 ft (610 mm).

At 9 cu ft (0.25 m³), the integral bin accommodates the contents of approximately one-third of a bulk bag measuring 3 x 3 x 3 ft (1 x 1 x 1 m), or several typical 50 lb (23 kg) bags, depending on bulk density.

A specialized BEV-CON™ screw within the straight conveyor tube is engineered to move a range of difficult-to-convey bulk materials that tend to cake, pack, smear or plug, as well as fragile products prone to breakage, with no separation of blends.

With the exception of the polymer tube, all material contact surfaces are of stainless steel finished to food, pharmaceutical, dairy or industrial standards for rapid wash down and/or corrosion resistance.



Low profile, mobile flexible screw conveyor with integral 9 cu ft (0.25 m³) bin and straight BEV-CON™ screw fits below mezzanines and other low headroom areas, discharging at locations throughout the plant.

flexicon®

USA

FLEXICON CORPORATION
Tel: +1 610 814 2400
E-mail: sales@flexicon.com
Web: www.flexicon.com