

Popular Models Now in Stock for Rush Shipment



Flexicon maintains fully assembled units and/or ready-to-assemble components to deliver popular models of Flexible Screw Conveyors, Bulk Bag Dischargers and Bulk Bag Conditioners on a rush basis.

QUICK-SHIP Flexible Screw Conveyors are offered in any length from 10 to 40 ft (3 to 12 m), in diameters from 2.625 to 4.5 in. (65 to 115 mm) OD



FLEXICON® Flexible Screw Conveyors

(Limited to North/Central/South America and Europe) Lead time is 1-2 working weeks*

STANDARD EQUIPMENT

- Stainless steel floor hopper
- Stainless steel screws in a range of geometries depending on model and material to be conveyed per factory recommendation
- TEFC or wash-down duty motor
- 45 or 90 degree discharge transition adapters
- UL Listed control panel, NEMA 4 (also built to CSA standards, uninspected)
- Carbon steel construction with durable industrial finish for non-product contact components and stainless steel for product contact surfaces

OPTIONAL EQUIPMENT

- Vibratory flow-promotion
- Hopper cover with unflanged inlet port
- Hopper screen
- Low level sensor, NEMA 4

BFF forklift load (left) and BFC electric hoist and trolley load (right). Both models shown with standard and optional equipment.



BULK-OUT® Bulk Bag Dischargers

(Limited to North/Central/South America and Europe) Lead time is 2-3 working weeks*

STANDARD EQUIPMENT

- Forklift-loaded BFF or electric hoist and trolley loaded BFC models
- Electric hoist and trolley (BFC model)
- Flow Flexer® bag activators
- Carbon steel construction with durable industrial finish for non-product contact components and stainless steel for product contact surfaces

OPTIONAL EQUIPMENT

- POP-TOP™ extension arms (BFF model)
- POWER-CINCHER® flow control valve
- TELE-TUBE® telescoping tube with SPOUT-LOCK® clamp ring
- Single filter BAG-VAC® dust collector, TEFC or wash-down duty motor
- UL Listed control panel, NEMA 4 (also built to CSA standards, uninspected)
- Magnehelic differential pressure gauge
- Flexible screw conveyor with hopper

BCF forklift load bulk bag conditioner



BLOCK-BUSTER® Bulk Bag Conditioners

(Limited to North/Central/South America and Europe) Lead time is 3-4 working weeks*

STANDARD EQUIPMENT

- Two opposing hydraulic rams with contoured conditioning plates delivering user-adjustable force
- Programmable scissor lift with turntable for conditioning of bags on all sides at all heights
- Bulk bag weight capacity of 4000 lb (1800 kg)
- Accommodates bulk bags 36 to 72 in. (965 to 1850 mm) tall, seam widths to 36 in. (915 mm) and filled widths to 48 in. (1220 mm)
- Accommodates pallet sizes to 48 in. (1220 mm) square
- Heavy duty carbon steel frame with durable industrial coating
- Four-sided safety enclosure with hinged access doors with NEMA 4 interlock switch
- Hydraulic power unit
- UL Listed control panel, NEMA 4 (also built to CSA standards, uninspected)

*PLEASE NOTE: Lead times are following receipt of order once payment terms have been met.

Further to the QUICK SHIP program, we offer an alternative program which provides additional equipment components and a choice of sanitary product contact finish levels for use with Flexible Screw Conveyors and Bulk Bag Dischargers. Manual Bag Dumping Stations with or without integrated dust collection are also available. Lead time is 4-5 or 5-6 working weeks dependent upon finish level. Please contact your Flexicon Sales Engineer for more details.

USA
sales@flexicon.com
1 888 FLEXICON

flexicon®
.com

UK +44 1227 374710
SPAIN +34 930 020 509
FRANCE +33 7 61 36 56 12
GERMANY +49 173 900 78 76



See the full range of equipment at flexicon.com: Flexible Screw Conveyors, Tubular Cable Conveyors, Pneumatic Conveying Systems, Bulk Bag Unloaders, Bulk Bag Conditioners, Bulk Bag Fillers, Bag Dump Stations, Drum/Box/Container Dumpers, Weigh Batching and Blending Systems, and Automated Plant-Wide Bulk Handling Systems